



(19)

(11) Publication number: **0**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **01154279**(51) Intl. Cl.: **A61M 1/18**(22) Application date: **16.06.89**

<p>(30) Priority:</p> <p>(43) Date of application publication: 25.01.91</p> <p>(84) Designated contracting states:</p>	<p>(71) Applicant: TERUMO CORP</p> <p>(72) Inventor: MURAMOTO TOMONO SAKAI SATORU</p> <p>(74) Representative:</p>
-------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------

**(54) METHOD AND DEVICE
FOR DETECTING LEAK OF
HOLLOW FIBER
MEMBRANE TYPE LIQUID
PROCESSOR**

(57) Abstract:

PURPOSE: To detect the presence and absence of leak even when a hollow fiber membrane with a full extended tip exists in a hollow fiber bundle by detecting a moving distance in a route means on a boundry between charged water and gas with pressure drop by using a gauge or a sensor.

CONSTITUTION: A gas lead-in port opening/closing valve 9a is closed and a charging water lead-in port opening/closing valve 8a is opened. Then, charging water (RO water) is charged through a route tube body 7 and a blood port 5b into a hollow fiber membrane 2a. Continuously, the opening/closing valve 8a is closed and the gas lead-in port opening/closing valve 9a is opened.

BEST AVAILABLE COPY

Then, pressurization with high pressure is executed by a pressurizing pump. After the pressurization, the opening/closing valve 9a is closed and left for prescribed time. When there is a pin hole, etc., in any hollow fiber membrane 2a, the RO water is leaked from the part and the internal pressure falls down by the leakage. Then, in a leak discriminating part A, a boundary 11 between the RO water and air is moved to the side of the hollow fiber membrane 2a. Accordingly, by detecting the moving quantity of this boundary 11 with a gauge 12 and calculating the moving quantity for each unit time, the presence and absence of the leak can be discriminated.

COPYRIGHT: (C)1991,JPO&Japio

